



Core Alignment fusion splicer

Z1C



Fast, Capable, Practical

Fast Splicing 6sec / Heating 20sec



Detachable Case
for Working Tray



Touch Screen
Control Panel



Durable & Rugged

Specifications

Items	Z1C
Optical fiber requirements	Material Silica glass
	Fiber count / Profile types Single / SMF (G.652), MMF (G.651), DSF (G.653), NZDSF (G.655), BIF (G.657)
	Fiber diameter Cladding diameter : 80 -150µm, Coating diameter: 100 - 1,000µm
Standard performance	Cleave length 5 - 16mm with coating clamp
	Splice loss (typical) *1 SMF : 0.02dB, MMF : 0.01dB, DSF : 0.04dB, NZDSF : 0.04dB
	Return loss (typical) 60dB or greater
	Splice time (typical) 6sec (SM G652 Quick Mode), 8sec (Auto Mode)
	Heating time (typical) 20sec (FPS-61-2.6 sleeve, Slim 60mm Quick Mode)
	Splice & Heat cycles per battery full charge *2 Approx. 230 (BU-11)
	Fiber view & magnification 2 CMOS cameras observation, 350X (zoom : 700X) for X or Y single axis view, 88X for both X & Y dual axis view
Programs	Proof test 1.96 - 2.09N
	Applicable sleeve length Up to 60mm sleeves
Functions	Splice programs Max. 300, 40 are pre-optimised, 260 editable by user
	Heating programs Max. 100, 19 are pre-optimised, 81 editable by user
Size / Weight	Splice image capture / Splice data storage 200 images/10,000 splice data (internal memory only) 50,200/20,000 (with 8GB SD card)
	Attenuation splicing 0.1dB to 15dB in 0.1dB increments
	Universal clamps Provided, 250µm, 900µm tight & loose buffer fiber
	Reversible coating clamps Provided
	Onboard user training video Provided
	Automatic fiber identification SMF / MMF / Other
Terminals	Automatic arc calibration Automatically compensates for environmental condition changes
	Size 120(W) x 154(D) x 130(H) mm (without anti-shock rubber)
Power supply	Weight 1.7kg (without Battery) / 1.9kg (with Battery BU-11S) / 2.0kg (with Battery BU-11)
	Monitor 4.1" touch screen color LCD display
Operating condition	DC output DC 12V (for JR-6)
	USB port USB 2.0 (mini-B type)
Storage condition	Storage media SD / SDHC memory card Max. 32GB
	AC input AC 100 - 240V, 50/60Hz (ADC-1430S)
Electrode life *3	DC input DC 10 - 15V
	Battery pack Li-ion 11.1V, 4,600mAh (BU-11) / Li-ion 11.1V, 2,300mAh (BU-11S)
Software updates	Altitude : 0 - 6,000m, Temperature : -10 - +50°C, Humidity : 0 - 95% (non-condensing), Wind velocity : up to 15m/sec
Data management	Temperature : -40 - +80°C, Humidity : 0 - 95% (non-condensing), Battery : -20 - +30°C (long term)
	6,000 arc discharges
	Internet
	Can be stored, edited and analyzed by dedicated PC software

*1 : Average value of the final inspection in room temperature with Sumitomo identical fiber.

Measured by cut-back method relevant to ITU-T and IEC standards.

*2 : Splice & Heat cycles may vary depending on the battery status and the operating environment.

*3 : Achieved in lab condition. Electrode life may vary depending on the operating environment.

Environmental Durability*

Test details	Test details
Shock resistance	Drop from 76cm on 5 faces (excluding top face)
Water resistance	Equivalent to IPX2 (Operates normally after being exposed to water dripping at 3mm/min, for at least 2.5 min on each of 4 surfaces tilted at 15°)
Dust resistance	Equivalent to IP5X (Operates normally after 8 hours in a test chamber with circulating dust particles smaller than 75µm)

*Splicer operation after shock, water or dust tests, was confirmed under battery power, by Sumitomo.

Does not guarantee the product will not be damaged by these conditions.

Basic Accessories

Part name	Part No.	Qty.
AC adapter	ADC-1430 series	1 pc
AC power cord	PC-AC9	1 pc
Cooling tray	—	1 pc
Battery pack	BU-11	1 pc
Spare electrode	ER-10	1 pair
Operating CD manual	—	1 pc
Quick reference guide	—	1 pc
Carrying case with worktable	CC-Z1 / CC-81	1 pc
Hand strap	—	1 pc
USB cable	—	1 pc

Items listed in Basic Accessories are always included with the splicer body. Overall kit content may vary regionally. Please check with your local authorized reseller to confirm kit content in your region.

Accessories

Part name	Part No.	Remarks	
Accessories for Splicer	FHS-025	For φ0.25mm single fiber	
	FHS-09	For φ0.9mm single fiber	
	FHS-025/LB5	For 0.9mm loose buffered single fiber	
	FHD-1	For drop/indoor cable (Cable size : typical 2.0 x 3.1 or 2.6mm)	
	1SM-ST	For indoor cable (Cable size : typical 1.6 x 2.0mm)	
	FHC-3	For 3mm cable	
Accessories	Lynx2-UML-S	For φ3mm cord and φ0.9mm single fiber	
	Battery pack	BU-11/11S	Li-ion 4,600mAh BU-11, 2,300mAh BU-11S
	Battery charger	BC-11	—
	Car battery cable	PCV-11	For car battery operation (cigarette socket type)
	V-groove cleaning brush	VGT-2	Brush for cleaning V-groove
	Electrode	ER-10	—
	Handheld fiber cleaver	FC-8R-FC	Automatic blade rotation cleaver with cleave counter
	Fiber cleaver	FC-8R-F	Automatic blade rotation cleaver
	Jacket remover	SFC-S	Table-top high precision cleaver
	Loose tube cutter	JR-M03	Jacket remover for single fiber
Alcohol dispenser	LTC-01	—	
Fiber protection sleeve	HR-3	—	
	FPS-1	60mm, diameter after shrink approx. φ3.2mm	
	FPS-40	40mm, diameter after shrink approx. φ3.2mm	
	FPS-61-2.6	61mm, diameter after shrink approx. φ2.6mm	



Carrying case with worktable
CC-Z1 / CC-81




Table-top cleaver
SFC-S



Handy cleaver
FC-8R series



Jacket remover
JR-M03



Available for
Lynx-Custom Fit™
Splice-On Connector



Electrode
ER-10

SUMITOMO ELECTRIC INDUSTRIES, LTD.

Tokyo (Japan)

Sumitomo Electric Industries, Ltd.

Akasaka Center Building, 1-3-13, Motoakasaka,

Minato-ku, Tokyo, 107-8468, JAPAN

TEL: +81-3-6406-2666

<http://global-sei.com/sumitomo-electric-splicers/>

■ Specifications are subject to change without prior notice.

Designed in Japan
OZ1C01-INDIA-EN003(2017,04)
(TP)